



SAFETY DATA SHEET

Prepared to U.S. OSHA, CMA, ANSI, Canadian WHMIS, the Korean ISHA (Notice 2009-68), the Japanese Industrial Standard JIS Z 7250: 2000, Mexican NOM018-STPS 2000, SPRING Singapore, and the Global Harmonization Standard

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY UNDERTAKING

IDENTIFICATION OF THE MIXTURE

TRADE/MATERIAL NAME: **SpecSeal® Powershield Box Insert**

RELEVANT USE of the SUBSTANCE: Firestop Device

USES ADVISED AGAINST: None

SUPPLIER/MANUFACTURER'S NAME: **Specified Technologies, Inc.**

Address: 210 Evans Way,
Somerville, New Jersey 08876
(908) 526-8000 (8:00am to 5:00pm Eastern Standard Time)

Business Phone: U.S., Canada: 1-800-255-3924 (24 hrs)

Emergency Phone: International: +1-813-248-0585 (Collect-24 hrs)

EMAIL of Competent Person for Information on SDS: techserv@stifirestop.com

NOTE: ALL United States Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalent Standards, Canadian WHMIS [Controlled Products Regulations], Mexican NOM018-STPS 2000, SPRING Singapore, and Japanese JIS Z7250 required information is included in appropriate sections based on the U.S. ANSI Z400.1-2010 format. This product has been classified in accordance with the hazard criteria of the countries listed above.

This product is defined as an "Article" under the U.S. Federal OSHA Hazard Communication Standard (29 CFR 1910.1200), EU Directives, and the Canadian Workplace Hazardous Materials Standard. Refer to Section 15 (Regulatory Information) for specific regulatory citations. As articles, this product presents negligible health and physical hazards under reasonably anticipated circumstances of use. Subsequently, a Material Safety Data Sheet is not required under Standards cited above. This document is prepared to provide persons using this product with additional safety information.

2. HAZARD IDENTIFICATION

GLOBAL HARMONIZATION AND EU CLP REGULATION (EC) 1272/2008 LABELING AND CLASSIFICATION: This product is an article and is not required to be classified under CLP Regulation (EC) 1272/2008.

EU 67/548/EEC LABELING AND CLASSIFICATION: This product is an article and is not required to be classified under European Community Council Directive 67/548/EEC or subsequent Directives.

KOREAN ISHA (Notice 2009-68) LABELING AND CLASSIFICATION: As an article, this product is not subject to ISHA Notice 2009-68.

3. COMPOSITION and INFORMATION ON INGREDIENTS

This product is an article and as such no components of this product pose a hazard; no component information is given in this SDS.

4. FIRST-AID MEASURES

Skin Exposure: As an article, no need for first aid is anticipated.

Inhalation: As an article, no need for first aid is anticipated.

Eye Exposure: As an article, no need for first aid is anticipated.

Ingestion: As an article, no need for first aid is anticipated.

5. FIRE-FIGHTING MEASURES

FIRE EXTINGUISHING MEDIA: Use extinguishing materials suitable for the surrounding area.

UNSUITABLE FIRE EXTINGUISHING MEDIA: None known.

UNUSUAL FIRE AND EXPLOSION HAZARDS: This product is formulated to be non-flammable and non-combustible.

SPECIAL PROTECTIVE ACTIONS FOR FIRE-FIGHTERS: No Special protective actions for fire-fighters are anticipated.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS AND EMERGENCY PROCEDURES: Not applicable.

PERSONAL PROTECTIVE EQUIPMENT: Not applicable.

METHODS FOR CLEAN-UP AND CONTAINMENT: Not applicable.

ENVIRONMENTAL PRECAUTIONS: Not applicable.

7. HANDLING and STORAGE

PRECAUTIONS FOR SAFE HANDLING: No special requirements.

CONDITIONS FOR SAFE STORAGE: No special requirements.

8. EXPOSURE CONTROLS - PERSONAL PROTECTION

EXPOSURE LIMITS/CONTROL PARAMETERS: As an article which does not release or otherwise result in exposure to hazardous chemicals under normal use; no personal protective equipment (PPE) are required.

9. PHYSICAL and CHEMICAL PROPERTIES

FORM: Solid.

ODOR: Not available.

FLAMMABLE LIMITS (in air by volume, %): Not available.

DECOMPOSITION TEMPERATURE: Not available.

AUTOIGNITION TEMPERATURE: Not available.

FREEZING/MELTING POINT: Not available.

VAPOR PRESSURE: Not applicable.

VAPOR DENSITY (air = 1): Not applicable.

EVAPORATION RATE (n-BuAc = 1): Not applicable.

SOLUBILITY IN WATER: Insoluble.

COEFFICIENT WATER/OIL DISTRIBUTION: Not established.

COLOR: Black with Red Label.

ODOR THRESHOLD: Not available.

OXIDIZING PROPERTIES: Not applicable.

PERCENT VOLATILE: 0

FLASH POINT: Not available.

BOILING POINT: Not applicable.

SPECIFIC GRAVITY (water = 1): Not applicable.

CARB VOC: Not applicable.

SCAQMD (U.S. EPA Method 24): Not applicable.

SOLUBILITY IN SOLVENTS: Not applicable.

pH: Not applicable.

10. STABILITY and REACTIVITY

CHEMICAL STABILITY: This product is stable when properly stored at normal temperatures.

11. TOXICOLOGICAL INFORMATION

SYMPTOMS OF EXPOSURE BY ROUTE OF EXPOSURE:

Inhalation: Due to the form of the product, inhalation is unlikely.

Contact with Skin or Eyes: Due to the form of the product, contact with the eyes is unlikely.

Skin Absorption: Due to form of product, skin absorption is not a likely route of exposure.

Ingestion: Ingestion is not a likely route of exposure, due to the form of the product.

Injection: Injection is not likely, due to the form of the product.

12. ECOLOGICAL INFORMATION

MOBILITY: As an article, this product will not be mobile in soil.

PERSISTENCE AND BIODEGRADABILITY: No specific information is available regarding persistence and biodegradability.

BIO-ACCUMULATION POTENTIAL: This product has not been tested for bio-accumulation potential.

ECOTOXICITY: This product has not been tested for aquatic or animal toxicity. All releases to terrestrial, atmospheric and aquatic environments should be avoided.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS: Waste disposal must be in accordance with appropriate Federal, State, and local regulations.
U.S. EPA WASTE NUMBER: Not applicable.

14. TRANSPORTATION INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION REGULATIONS: This product is not classified as dangerous goods, per U.S. DOT regulations, under 49 CFR 172.101.

TRANSPORT CANADA TRANSPORTATION OF DANGEROUS GOODS REGULATIONS: This product is not classified as Dangerous Goods, per regulations of Transport Canada.

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA): This product is not classified as dangerous goods under rules of IATA.

INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION: This product is not classified as Dangerous Goods by the International Maritime Organization.

OFFICIAL MEXICAN STANDARD; REGULATION FOR THE TRANSPORT OF DANGEROUS GOODS AND RESIDUES: This product is not classified as Dangerous Goods, per transport regulations of Mexico.

SINGAPORE STANDARD 286: PART A: This product has no requirements under the Specification for Caution Labeling for Hazardous Substances, Part 4: Marking of Packages, Containers and Vehicles, as it does not meet the criteria for any hazard class under this regulation.

TRANSPORT IN BULK ACCORDING TO THE IBC CODE: See the information under the individual jurisdiction listings for IBC information.

ENVIRONMENTAL HAZARDS: This material does not meet the criteria of environmentally hazardous according to the criteria of the UN Model Regulations (as reflected in the IMDG Code, ADR, RID, and ADN) and is not listed in Annex III under MARPOL 73/78.

15. REGULATORY INFORMATION

UNITED STATES REGULATIONS:

U.S. SARA Reporting Requirements: As an article, this product is not subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

U.S. SARA Hazard Categories (Section 311/312, 40 CFR 370-21): ACUTE: No; CHRONIC: No; FIRE: No; REACTIVE: No; SUDDEN RELEASE: No

U.S. SARA Threshold Planning Quantity (TPQ): As an article, this product is not subject to Threshold Planning Quantities, per 40 CFR 370.20.

U.S. CERCLA Reportable Quantity (RQ): Not applicable.

U.S. TSCA Inventory Status: Components of this product are listed on the TSCA Inventory.

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65): No component is on the California Proposition 65 lists.

CANADIAN REGULATIONS:

Canadian DSL/NDSL Inventory Status: Components are on the DSL or NDSL Inventories.

Canadian Environmental Protection Act (CEPA) Priorities Substances Lists: Components are not on the CEPA Priorities Substances Lists.

Canadian WHMIS Classification and Symbols: As an article, this product is not subject the Controlled Product Regulations.

CHINESE REGULATIONS:

Chinese Inventory of Existing Chemical Substances Status: As an article, this product is not subjected to requirements under the Chinese Inventory of Existing Chemical Substances (IECSC).

JAPANESE REGULATIONS:

Japanese ENCS: As an article, this product is not subjected to requirements under ENCS Inventory.

Japanese Ministry of Economy, Trade, and Industry (METI) Status: As an article, this product is not subjected to requirements under the Japanese METI.

Poisonous and Deleterious Substances Control Law: As an article, this product is not subjected to requirements under the Poisonous and Deleterious Substances Control Law.

KOREAN REGULATIONS:

Korean Existing Chemicals List (ECL) Status: As an article, this product is not subjected to requirements under the Korean ECL Inventory.

MEXICAN REGULATIONS:

Mexican Workplace Regulations (NOM-018-STPS-2000): This product is not classified as hazardous.

SINGAPORE REGULATIONS:

List of Controlled Hazardous Substances: As an article, this product is not subjected to requirements under the Singapore List of Controlled Substances.

Code of Practice on Pollution Control Requirements: As an article, this product is not subjected to requirements under the Singapore Code of Practice on Pollution Control.

TAIWANESE REGULATIONS:

Taiwan Existing Chemical Substances Inventory Status: As an article, this product is not subjected to requirements under the Taiwan Existing Chemicals List.

16. OTHER INFORMATION

REFERENCES AND DATA SOURCES: Contact the supplier for information.

METHODS OF EVALUATING INFORMATION FOR THE PURPOSE OF CLASSIFICATION: Criteria of the GHS were used for classification.

PREPARED BY: CHEMICAL SAFETY ASSOCIATES, Inc. • PO Box 1961, Hilo, HI 96721-1961 • (800) 441-3365

DATE OF PRINTING: January 9, 2017

REVISED: January 3, 2017

REVISION DETAILS: Reviewed January 3, 2017, no changes.

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these, which are commonly used, include the following:

CAS #: This is the Chemical Abstract Service Number that uniquely identifies each constituent.

EXPOSURE LIMITS IN AIR:

CEILING LEVEL: The concentration that shall not be exceeded during any part of the working exposure.

DFG MAKs: Federal Republic of Germany Maximum Concentration Values in the workplace. Exposure limits are given as TWA (Time-Weighted Average) or PEAK (short-term exposure) values.

DFG MAK Germ Cell Mutagen Categories: **1:** Germ cell mutagens that have been shown to increase the mutant frequency in the progeny of exposed humans. **2:** Germ cell mutagens that have been shown to increase the mutant frequency in the progeny of exposed mammals. **3A:** Substances that have been shown to induce genetic damage in germ cells of human of animals, or which produce mutagenic effects in somatic cells of mammals *in vivo* and have been shown to reach the germ cells in an active form. **3B:** Substances that are suspected of being germ cell mutagens because of their genotoxic effects in mammalian somatic cell *in vivo*; in exceptional cases, substances for which there are no *in vivo* data, but that are clearly mutagenic *in vitro* and structurally related to known *in vivo* mutagens. **4:** Not applicable (Category 4 carcinogenic substances are those with non-genotoxic mechanisms of action. By definition, germ cell mutagens are genotoxic. Therefore, a Category 4 for germ cell mutagens cannot apply. At some time in the future, it is conceivable that a Category 4 could be established for genotoxic substances with primary targets other than DNA [e.g. purely aneugenic substances] if research results make this seem sensible.) **5:** Germ cell mutagens, the potency of which is considered to be so low that, provided the MAK value is observed, their contribution to genetic risk for humans is expected not to be significant.

DFG MAK Pregnancy Risk Group Classification: **Group A:** A risk of damage to the developing embryo or fetus has been unequivocally demonstrated. Exposure of pregnant women can lead to damage of the developing organism, even when MAK and BAT (Biological Tolerance Value for Working Materials) values are observed. **Group B:** Currently available information indicates a risk of damage to the developing embryo or fetus must be considered to be probable. Damage to the developing organism cannot be excluded when pregnant women are exposed, even when MAK and BAT values are observed. **Group C:** There is no reason to fear a risk of damage to the developing embryo or fetus when MAK and BAT values are observed. **Group D:** Classification in one of the groups A–C is not yet possible because, although the data available may indicate a trend, they are not sufficient for final evaluation.

IDLH: Immediately Dangerous to Life and Health. This level represents a concentration from which one can escape within 30-minutes without suffering escape-preventing or permanent injury.

LOQ: Limit of Quantitation.

NE: Not Established. When no exposure guidelines are established, an entry of NE is made for reference.

NIC: Notice of Intended Change.

NIOSH CEILING: The exposure that shall not be exceeded during any part of the workday. If instantaneous monitoring is not feasible, the ceiling shall be assumed as a 15-minute TWA exposure (unless otherwise specified) that shall not be exceeded at any time during a workday.

NIOSH RELs: NIOSH's Recommended Exposure Limits.

PEL: OSHA's Permissible Exposure Limits. This exposure value means exactly the same as a TLV, except that it is enforceable by OSHA. The OSHA Permissible Exposure Limits are based in the 1989 PELs and the June, 1993 Air Contaminants Rule (Federal Register: 58: 35338-35351 and 58: 40191). Both the current PELs and the vacated PELs are indicated. The phrase, "Vacated 1989 PEL" is placed next to the PEL that was vacated by Court Order.

SKIN: Used when there is a danger of cutaneous absorption.

STEL: Short Term Exposure Limit, usually a 15-minute time-weighted average (TWA) exposure that should not be exceeded at any time during a workday, even if the 8-hr TWA is within the TLV-TWA, PEL-TWA or REL-TWA.

TLV: Threshold Limit Value. An airborne concentration of a substance that represents conditions under which it is generally believed that nearly all workers may be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour.

TWA: Time Weighted Average exposure concentration for a conventional 8-hr (TLV, PEL) or up to a 10-hr (REL) workday and a 40-hr workweek.

WEEL: Workplace Environmental Exposure Limits from the AHA.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS:

This rating system was developed by the National Paint and Coating Association and has been adopted by industry to identify the degree of chemical hazards.

HEALTH HAZARD: 0 Minimal Hazard: No significant health risk, irritation of skin or eyes not anticipated. *Skin Irritation:* Essentially non-irritating. Mechanical irritation may occur. PII or Draize = 0. *Eye Irritation:* Essentially non-irritating, minimal effects clearing in < 24 hours. Mechanical irritation may occur. Draize = 0. *Oral Toxicity LD₅₀ Rat:* > 5000 mg/kg. *Dermal Toxicity LD₅₀ Rat or Rabbit:* > 2000 mg/kg. *Inhalation Toxicity 4-hrs LC₅₀ Rat:* > 20 mg/L. **1 Slight Hazard:** Minor reversible injury may occur; may irritate the stomach if swallowed; may defat the skin and exacerbate existing dermatitis. *Skin Irritation:* Slightly or mildly irritating. PII or Draize > 0 < 5. *Eye Irritation:* Slightly to mildly irritating, but reversible within 7 days. Draize > 0 ≤ 25. *Oral Toxicity LD₅₀ Rat:* > 500–5000 mg/kg. *Dermal Toxicity LD₅₀ Rat or Rabbit:* > 1000–2000 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* > 2–20 mg/L. **2 Moderate Hazard:** Temporary or transitory injury may occur; prolonged exposure may affect the CNS. *Skin Irritation:* Moderately irritating; primary irritant; sensitizer. PII or Draize ≥ 5, with no destruction of dermal tissue. *Eye Irritation:* Moderately to severely irritating; reversible corneal opacity; corneal involvement or irritation clearing in 8–21 days. Draize = 26–100, with reversible effects. *Oral Toxicity LD₅₀ Rat:* > 50–500 mg/kg. *Dermal Toxicity LD₅₀ Rat or Rabbit:* > 200–1000 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* > 0.5–2 mg/L. **3 Serious Hazard:** Major injury likely unless prompt action is taken and medical treatment is given; high level of toxicity; corrosive. *Skin Irritation:* Severely irritating and/or corrosive; may cause destruction of dermal tissue, skin burns, and dermal necrosis. PII or Draize > 5–8, with destruction of tissue. *Eye Irritation:* Corrosive, irreversible destruction of ocular tissue; corneal involvement or irritation persisting for more than 21 days. Draize > 80 with effects irreversible in 21 days. *Oral Toxicity LD₅₀ Rat:* > 1–50 mg/kg. *Dermal Toxicity LD₅₀ Rat or Rabbit:* > 20–200 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* > 0.05–0.5 mg/L. **4 Severe Hazard:** Life-threatening; major or permanent damage may result from single or repeated exposures; extremely toxic; irreversible injury may result from brief contact. *Skin Irritation:* Not appropriate. Do not rate as a 4, based on skin irritation alone. *Eye*

Irritation: Not appropriate. Do not rate as a 4, based on eye irritation alone. *Oral Toxicity LD₅₀ Rat:* ≤ 1 mg/kg. *Dermal Toxicity LD₅₀ Rat or Rabbit:* ≤ 20 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* ≤ 0.05 mg/L.

FLAMMABILITY HAZARD: 0 Minimal Hazard: Materials that will not burn in air when exposure to a temperature of 815.5°C (1500°F) for a period of 5 minutes.

FLAMMABILITY HAZARD (continued): 1 Slight Hazard: Materials that must be pre-heated before ignition can occur. Material requires considerable pre-heating, under all ambient temperature conditions before ignition and combustion can occur. This usually includes the following: Materials that will burn in air when exposed to a temperature of 815.5°C (1500°F) for a period of 5 minutes or less; Liquids, solids and semisolids having a flash point at or above 93.3°C (200°F) (i.e. OSHA Class III B); and Most ordinary combustible materials (e.g. wood, paper, etc.). **2 Moderate Hazard:** Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not, under normal conditions, form hazardous atmospheres in air, but under high ambient temperatures or moderate heating may release vapor in sufficient quantities to produce hazardous atmospheres with air. This usually includes the following: Liquids having a flash-point at or above 37.8°C (100°F); Solid materials in the form of coarse dusts that may burn rapidly but that generally do not form explosive atmospheres; **3 (continued):** Solid materials in a fibrous or shredded form that may burn rapidly and create flash fire hazards (e.g. cotton, sisal, hemp); and Solids and semisolids (e.g. viscous and slow flowing as asphalt) that readily give off flammable vapors. **3 Serious Hazard:** Liquids and solids that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures, or, unaffected by ambient temperature, are readily ignited under almost all conditions. This usually includes the following: Liquids having a flash point below 22.8°C (73°F) and having a boiling point at or above 38°C (100°F) and those liquids having a flash point at or above 22.8°C (73°F) and below 37.8°C (100°F) (i.e. OSHA Class IB and IC); Materials that on account of their physical form or environmental conditions can form explosive mixtures with air and are readily dispersed in air (e.g., dusts of combustible solids, mists or droplets of flammable liquids); and Materials that burn extremely rapidly, usually by reason of self-contained oxygen (e.g. dry nitrocellulose and many organic peroxides). **4 Severe Hazard:** Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air, and that will burn readily. This usually includes the following: Flammable gases; Flammable cryogenic materials; Any liquid or gaseous material that is liquid while under pressure and has a flash point below 22.8°C (73°F) and a boiling point below 37.8°C (100°F) (i.e. OSHA Class IA); and Materials that ignite spontaneously when exposed to air at a temperature of 54.4°C (130°F) or below (pyrophoric).

PHYSICAL HAZARD: 0 Water Reactivity: Materials that do not react with water. *Organic Peroxides:* Materials that are normally stable, even under fire conditions and will not react with water. *Explosives:* Substances that are Non-Explosive. *Compressed Gases:* No Rating. *Pyrophorics:* No Rating. *Oxidizers:* No 0 rating. *Unstable Reactives:* Substances that will not polymerize, decompose, condense, or self-react. **1 Water Reactivity:** Materials that change or decompose upon exposure to moisture. *Organic Peroxides:* Materials that are normally stable, but can become unstable at high temperatures and pressures. These materials may react with water, but will not release energy violently. *Explosives:* Division 1.5 & 1.6 explosives. Substances that are very insensitive explosives or that do not have a mass explosion hazard. *Compressed Gases:* Pressure below OSHA definition. *Pyrophorics:* No Rating. *Oxidizers:* Packaging Group III oxidizers; Solids: any material that in either concentration tested, exhibits a mean burning time less than or equal to the mean burning time of a 3:7 potassium bromate/cellulose mixture and the criteria for Packing Group I and II are not met. Liquids: any material that exhibits a mean pressure rise time less than or equal to the pressure rise time of a 1:1 nitric acid (65%)/cellulose mixture and the criteria for Packing Group I and II are not met. *Unstable Reactives:* Substances that may decompose, condense, or self-react, but only under conditions of high temperature and/or pressure and have little or no potential to cause significant heat generation or explosion hazard. Substances that readily undergo hazardous polymerization in the absence of inhibitors. **2 Water Reactivity:** Materials that may react violently with water. *Organic Peroxides:* Materials that, in themselves, are normally unstable and will readily undergo violent chemical change, but will not detonate. These materials may also react violently with water. *Explosives:* Division 1.4 explosives. Explosive substances where the explosive effects are largely confined to the package and no projection of fragments of appreciable size or range are expected. An external fire must not cause virtually instantaneous explosion of almost the entire contents of the package. *Compressed Gases:* Pressurized and meet OSHA definition but < 514.7 psi absolute at 21.1°C (70°F) [500 psig]. *Pyrophorics:* No Rating. *Oxidizers:* Packing Group II oxidizers. Solids: any material that, either in concentration tested, exhibits a mean burning time of less than or equal to the mean burning time of a 2:3 potassium bromate/cellulose mixture and the criteria for Packing Group I are not met. Liquids: any material that exhibits a mean pressure rise time less than or equal to the pressure rise of a 1:1 aqueous sodium chlorate solution (40%)/cellulose mixture and the criteria for Packing Group I are not met. *Reactivities:* Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure, but have a low potential (or low risk) for significant heat generation or explosion. Substances that readily form peroxides upon exposure to air or oxygen at room temperature. **3 Water Reactivity:** Materials that may form explosive reactions with water. *Organic Peroxides:* Materials that are capable of detonation or explosive reaction, but require a strong initiating source or must be heated under confinement before initiation; or materials that react explosively with water. *Explosives:* Division 1.3 explosives. Explosive substances that have a fire hazard and either a minor blast hazard or a minor projection hazard or both, but do not have a mass explosion hazard. *Compressed Gases:* Pressure ≥ 514.7 psi absolute at 21.1°C (70°F) [500 psig]. *Pyrophorics:* No Rating. *Oxidizers:* Packing Group I oxidizers. Solids: any material that, in either concentration tested, exhibits a mean burning time less than the mean burning time of a 3:2 potassium bromate/cellulose mixture. Liquids: any material that spontaneously ignites when mixed with cellulose in a 1:1 ratio, or which exhibits a mean pressure rise time less than the pressure rise time of a 1:1 perchloric acid (50%)/cellulose mixture. *Unstable Reactives:* Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure and have a moderate potential (or moderate risk) to cause significant heat generation or explosion. **4 Water Reactivity:** Materials that react explosively with water without requiring heat or confinement. *Organic Peroxides:* Materials that are readily capable of detonation or explosive decomposition at normal temperature and pressures. *Explosives:* Division 1.1 & 1.2

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS (Continued):

explosives. Explosive substances that have a mass explosion hazard or have a projection hazard. A mass explosion is one that affects almost the entire load instantaneously. *Compressed Gases*: No Rating. *Pyrophorics*: Add to the definition of Flammability 4. *Oxidizers*: No 4 rating. *Unstable Reactives*: Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure and have a high potential (or high risk) to cause significant heat generation or explosion.

NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS:

HEALTH HAZARD: 0 Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials. Gases and vapors with an LC₅₀ for acute inhalation toxicity greater than 10,000 ppm. Dusts and mists with an LC₅₀ for acute inhalation toxicity greater than 200 mg/L. Materials with an LD₅₀ for acute dermal toxicity greater than 2000 mg/kg. Materials with an LD₅₀ for acute oral toxicity greater than 2000 mg/kg. Materials essentially non-irritating to the respiratory tract, eyes, and skin. **1** Materials that, under emergency conditions, can cause significant irritation. Gases and vapors with an LC₅₀ for acute inhalation toxicity greater than 5,000 ppm but less than or equal to 10,000 ppm. Dusts and mists with an LC₅₀ for acute inhalation toxicity greater than 10 mg/L but less than or equal to 200 mg/L. Materials with an LC₅₀ for acute dermal toxicity greater than 1000 mg/kg but less than or equal to 2000 mg/kg. Materials that slightly to moderately irritate the respiratory tract, eyes and skin. Materials with an LD₅₀ for acute oral toxicity greater than 500 mg/kg but less than or equal to 2000 mg/kg. **2** Materials that, under emergency conditions, can cause temporary incapacitation or residual injury. Gases with an LC₅₀ for acute inhalation toxicity greater than 3,000 ppm but less than or equal to 5,000 ppm. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than one-fifth its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 5000 ppm and that does not meet the criteria for either degree of hazard 3 or degree of hazard 4. Dusts and mists with an LC₅₀ for acute inhalation toxicity greater than 2 mg/L but less than or equal to 10 mg/L. Materials with an LD₅₀ for acute dermal toxicity greater than 200 mg/kg but less than or equal to 1000 mg/kg. Compressed liquefied gases with boiling points between -30°C (-22°F) and -55°C (-66.5°F) that cause severe tissue damage, depending on duration of exposure. Materials that are respiratory irritants. Materials that cause severe, but reversible irritation to the eyes or are lachrymators. Materials that are primary skin irritants or sensitizers. Materials whose LD₅₀ for acute oral toxicity is greater than 50 mg/kg but less than or equal to 500 mg/kg. **3** Materials that, under emergency conditions, can cause serious or permanent injury. Gases with an LC₅₀ for acute inhalation toxicity greater than 1,000 ppm but less than or equal to 3,000 ppm. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 3000 ppm and that does not meet the criteria for degree of hazard 4. Dusts and mists with an LC₅₀ for acute inhalation toxicity greater than 0.5 mg/L but less than or equal to 2 mg/L. Materials with an LD₅₀ for acute dermal toxicity greater than 40 mg/kg but less than or equal to 200 mg/kg. Materials that are corrosive to the respiratory tract. Materials that are corrosive to the eyes or cause irreversible corneal opacity. Materials corrosive to the skin. Cryogenic gases that cause frostbite and irreversible tissue damage. Compressed liquefied gases with boiling points below -55°C (-66.5°F) that cause frostbite and irreversible tissue damage. Materials with an LD₅₀ for acute oral toxicity greater than 5 mg/kg but less than or equal to 50 mg/kg.

HEALTH HAZARD (continued): 4 Materials that, under emergency conditions, can be lethal. Gases with an LC₅₀ for acute inhalation toxicity less than or equal to 1,000 ppm. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than ten times its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 1000 ppm. Dusts and mists whose LC₅₀ for acute inhalation toxicity is less than or equal to 0.5 mg/L. Materials whose LD₅₀ for acute dermal toxicity is less than or equal to 40 mg/kg. Materials whose LD₅₀ for acute oral toxicity is less than or equal to 5 mg/kg.

FLAMMABILITY HAZARD: 0 Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand. Materials that will not burn in air when exposed to a temperature of 816°C (1500°F) for a period of 5 minutes in accordance with Annex D of NFPA 704. **1** Materials that must be preheated before ignition can occur. Materials in this degree require considerable preheating, under all ambient temperature conditions, before ignition and combustion can occur. Materials that will burn in air when exposed to a temperature of 816°C (1500°F) for a period of 5 minutes in accordance with Annex D of NFPA 704. Liquids, solids, and semisolids having a flash point at or above 93.4°C (200°F) (i.e. Class IIIB liquids). Liquids with a flash point greater than 35°C (95°F) that do not sustain combustion when tested using the *Method of Testing for Sustained Combustibility*, per 49 CFR 173, Appendix H or the *UN Recommendations on the Transport of Dangerous Goods, Model Regulations* (current edition) and the related *Manual of Tests and Criteria* (current edition). Liquids with a flash point greater than 35°C (95°F) in a water-miscible solution or dispersion with a water non-combustible liquid/solid content of more than 85% by weight. Liquids that have no fire point when tested by ASTM D 92, *Standard Test Method for Flash and Fire Points by Cleveland Open Cup*, up to the boiling point of the liquid or up to a temperature at which the sample being tested shows an obvious physical change. Combustible pellets with a representative diameter of greater than 2 mm (10 mesh). Most ordinary combustible materials. Solids containing greater than 0.5% by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. **2** Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not under normal conditions form hazardous atmospheres with air, but under high ambient temperatures or under moderate heating could release vapor in sufficient quantities to produce hazardous atmospheres with air. Liquids having a flash point at or above 37.8°C (100°F) and below 93.4°C (200°F) (i.e. Class II and Class IIIA liquids). Solid materials in the form of powders or coarse dusts of representative diameter between 420 microns (40 mesh) and 2 mm (10 mesh) that burn rapidly but that generally do not form explosive mixtures with air. Solid materials in fibrous or shredded form that burn rapidly and create flash fire hazards, such as cotton, sisal, and hemp. Solids and semisolids that readily give off flammable vapors. Solids containing greater than 0.5% by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. **3** Liquids and solids that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures or, though unaffected by ambient temperatures, are readily ignited under almost all conditions. Liquids having a flash point below 22.8°C (73°F) and having a boiling point at or above 37.8°C (100°F) and those liquids having a flash point at or above 22.8°C (73°F) and below 37.8°C (100°F) (i.e. Class IB and IC liquids). Materials that on account of their physical form or environmental conditions can form explosive mixtures with air and are readily dispersed in air. Flammable or combustible dusts with representative diameter less than 420 microns (40 mesh).

NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS (continued):

Materials that burn with extreme rapidity, usually by reason of self-contained oxygen (e.g. dry nitrocellulose and many organic peroxides). Solids containing greater than 0.5% by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and will burn readily. Flammable gases. Flammable cryogenic materials. Any liquid or gaseous materials that is liquid while under pressure and has a flash point below 22.8°C (73°F) and a boiling point below 37.8°C (100°F) (i.e. Class IA liquids). Materials that ignite when exposed to air. Solids containing greater than 0.5% by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. **4** Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and will burn readily. Flammable gases. Flammable cryogenic materials. Any liquid or gaseous materials that is liquid while under pressure and has a flash point below 22.8°C (73°F) and a boiling point below 37.8°C (100°F) (i.e. Class IA liquids). Materials that ignite when exposed to air. Solids containing greater than 0.5 percent by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent.

INSTABILITY HAZARD: 0 Materials that in themselves are normally stable, even under fire conditions. Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) below 0.01 W/mL. Materials that do not exhibit an exotherm at temperatures less than or equal to 500°C (932°F) when tested by differential scanning calorimetry. **1** Materials that in themselves are normally stable, but that can become unstable at elevated temperatures and pressures. Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 0.01 W/mL and below 10 W/mL. **2** Materials that readily undergo violent chemical change at elevated temperatures and pressures. Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 10 W/mL and below 100W/mL. **3** Materials that in themselves are capable of detonation or explosive decomposition or explosive reaction, but that require a strong initiating source or that must be heated under confinement before initiation. Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 100 W/mL and below 1000 W/mL. Materials that are sensitive to thermal or mechanical shock at elevated temperatures and pressures. **4** Materials that in themselves are readily capable of detonation or explosive decomposition or explosive reaction at normal temperatures and pressures. Materials that are sensitive to localized thermal or mechanical shock at normal temperatures and pressures. Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) of 1000 W/mL or greater.

FLAMMABILITY LIMITS IN AIR:

Much of the information related to fire and explosion is derived from the National Fire Protection Association (NFPA). **Flash Point**: Minimum temperature at which a liquid gives off sufficient vapor to form an ignitable mixture with air near the surface of the liquid or within the test vessel used. **Autoignition Temperature**: Minimum temperature of a solid, liquid, or gas required to initiate or cause self-sustained combustion in air with no other source of ignition. **LEL**: Lowest concentration of a flammable vapor or gas/air mixture that will ignite and burn with a flame. **UEL**: Highest concentration of a flammable vapor or gas/air mixture that will ignite and burn with a flame.

TOXICOLOGICAL INFORMATION:

Human and Animal Toxicology: Possible health hazards as derived from human data, animal studies, or from the results of studies with similar compounds are presented. **LD₅₀**: Lethal Dose (solids & liquids) that kills 50% of the exposed animals. **LC₅₀**: Lethal Concentration (gases) that kills 50% of the exposed animals. **ppm**: Concentration expressed in parts of material per million parts of air or water. **mg/m³**: Concentration expressed in weight of substance per volume of air. **mg/kg**: Quantity of material, by weight, administered to a test subject, based on their body weight in kg. **TDLo**: Lowest dose to cause a symptom. **TCLo**: Lowest concentration to cause a symptom. **TD₀₁**, **LDLo**, and **LD₀₁**, or **TC**, **TCLo**, **LCLo**, and **LC₀₁**: Lowest dose (or concentration) to cause lethal or toxic effects. **Cancer Information**: **IARC**: International Agency for Research on Cancer. **NTP**: National Toxicology Program. **RTECS**: Registry of Toxic Effects of Chemical Substances. IARC and NTP rate chemicals on a scale of decreasing potential to cause human cancer with rankings from 1 to 4. Subrankings (2A, 2B, etc.) are also used. **Other Information**: **BEI**: ACGIH Biological Exposure Indices, represent the levels of determinants which are most likely to be observed in specimens collected from a healthy worker who has been exposed to chemicals to the same extent as a worker with inhalation exposure to the TLV.

ECOLOGICAL INFORMATION:

EC: Effect concentration in water. **BCF**: Bioconcentration Factor, which is used to determine if a substance will concentrate in life forms that consume contaminated plant or animal matter. **TLm**: Median threshold limit. **log K_{ow}** or **log K_{oc}**: Coefficient of Oil/Water Distribution is used to assess a substance's behavior in the environment.

REGULATORY INFORMATION:

U.S.:

EPA: U.S. Environmental Protection Agency. **ACGIH**: American Conference of Governmental Industrial Hygienists, a professional association that establishes exposure limits. **OSHA**: U.S. Occupational Safety and Health Administration. **NIOSH**: National Institute of Occupational Safety and Health, which is the research arm of OSHA. **DOT**: U.S. Department of Transportation. **SARA**: Superfund Amendments and Reauthorization Act. **ISCA**: U.S. Toxic Substance Control Act. **CERCLA**: Comprehensive Environmental Response, Compensation, and Liability Act. Marine Pollutant status according to the DOT; CERCLA or Superfund; and various state regulations. This section also includes information on the precautionary warnings that appear on the material's package label.

CANADA:

WHMIS: Canadian Workplace Hazardous Materials Information System. **TC**: Transport Canada. **DSL/NDL**: Canadian Domestic/Non-Domestic Substances List.

JAPAN:

METI: Ministry of Economy, Trade and Industry.